

KODAK PIXPRO AZ365

DIGITAL CAMERA



AZ365 ASTRO ZOOM

It's rare that cutting-edge technology and affordability come together seamlessly. The wait is over, meet the all new KODAK PIXPRO AZ365 Digital Camera, designed for the artist in us all. Express your creative side with stunning photos and video of those moments most special to you and yours. Easy to use features, brilliant color, clarity and detail are the cornerstones to what makes this bridge camera a must have for your everyday adventures, special moments and memories to last a family a lifetime. KODAK PIXPRO Cameras – Tell your story.

FEATURES:

- 36X Optical Zoom
- 24mm Wide Angle
- 16 Megapixels
- 3.0" LCD
- 720p HD Video
- OIS (Optical Image Stabilization)
- AA Batteries



Available Colors:

- BLACK
- RED
- WHITE

Images are simulated.

36X
OPTICAL
ZOOM

24mm
WIDE

16MP

3"
7.6cm

HD

Panorama
Capture



KODAK PIXPRO AZ365

DIGITAL CAMERA

SPECIFICATIONS	AZ365
Effective Image Sensor Pixels	16.15 Megapixels
Total Image Sensor Pixels	16.44 Megapixels [1/2.3" CCD]
Lens	
Focal Length	4.3 mm (Wide) — 154.8 mm (Tele)
[35mm film equivalent]	[24 mm (Wide) — 864 mm (Tele)]
F number	F3.0 (Wide) — F6.6 (Tele)
Lens Construction	11 groups 15 elements
Optical Zoom	36x
Focusing Range	Normal: (Wide) 50 cm — ∞, (Tele) 200 cm — ∞ Macro: 1.6 cm — ∞ (Wide Only)
Anti-Shake	OIS (Optical Image Stabilization)
Digital Zoom	4x Digital Zoom (Combined Zoom: 144x)
Number of Recording Pixels	
Still Image	(4:3) 16MP: 4608x3456, 10MP: 3648x2736, 5MP: 2592x1944, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 14MP: 4608x3072, (16:9) 12MP: 4608x2592, 2MP: 1920x1080
Movie	1280x720(30/15fps), 640x480(30fps)
Image Compression	Best, Fine, Normal
DCF, DPOF (Ver1.1) Support	Yes
File Format	
Still Image	Exif 2.3 (JPEG)
Movie	Movie Format: MOV (H.264), Audio: Linear PCM [Monaural]
Shooting Modes	Auto, P, S, A, M, Face Beautifier, Panorama, SCN [ASCN, Landscape, Sport, Sunset, Fireworks, Night Landscape, Snow, Children, Portrait, Party, Night Portrait, Pet], Movie, CS
Detection Features	Face, Smile, Blink, Cat, Dog
Photo Touch-up	Red-Eye Reduction, Skin Soften, Eye Brightening, Eye Enlargement, HDR
Panorama	0° - 180°
LCD Display	3.0 inch (460K Pixels)
ISO Sensitivity	Auto, ISO 80/100/200/400/800/1600/3200 (4M)
AF Method	Single AF, Multi-AF (TTL 9-point), Object Tracking, Face Detection
Exposure Metering Method	Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot (Fixed to Center of Frame), Face AE
Exposure Control Method	Program AE (AE-Lock Available), Shutter Priority AE, Aperture Priority AE
Exposure Compensation	+/- 2EV in 1/3 Step Increments
Shutter Speed	1/2000 - 30 Seconds
Continuous Shooting	Yes
Playback Modes	Single Photo, Index (9/16 Thumbnails) Slide Show, Date, Zoom (Approx. x2 - x8)
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Manual, Color Temperature Setting (1900K - 10000K)
Flash	
Flash Method	Pop-up (Manual)
Flash Modes	Auto, Red-Eye Reduction, Forced Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro
Shooting Range	(Wide) Approx. 0.5 m - 7.5 m (ISO800); (Tele) Approx. 1.2 m - 3.7 m (ISO800)
Recording Media	Internal Memory: Approx. 8MB SD/SDHC Card (Up to 32GB Support) [MMC Card not supported]
Other Features	Eye-Fi, PictBridge, ExifPrint Support, Multi-Language Support (27 Languages)
Jacks	AV-OUT/USB 2.0 (Micro 5 pin USB), HDMI (Type D)
Power	AA Alkaline Battery (x4) AA NiMH Battery (x4) (Not Included)
Shooting Capability (Battery Performance)	Approx. 280 Shots of Alkaline Battery (Based on CIPA Standards) Approx. 500 Shots of AA NiMH Battery (Based on CIPA Standards)
Operation Environment	Temperature: 32° - 104°F / 0° - 40°C, Humidity: 0 - 90%
Dimensions (WxHxD)	Approx. 4.50 x 3.21 x 3.32 in. / 114.3 x 81.6 x 84.4 mm (Based on CIPA Standards)
Weight	Approx. 15.38 oz. / 436 g (Body Only)
Supplied Accessories	AA Alkaline Battery(x4), USB Cable, Neck Strap, Lens Cover, Quick Start Guide, Warranty Card, Service Card

JK Imaging Ltd.

17239 So. Main Street, Gardena, CA 90248
(888) 978-0806

© 2017 JK Imaging, Ltd. The Kodak trademark, logo and trade dress are used under license from Eastman Kodak Company.
All information contained in this document is subject to change without notice. Document Number/Sequence: U.DIS.0021.0717.en.03

To learn more about KODAK PIXPRO Digital Cameras:
visit: kodakpixpro.com

