

# KODAK PIXPRO AZ401

## DIGITAL CAMERA



## AZ401 ASTRO ZOOM

Passion and performance go hand in hand with our KODAK PIXPRO AZ401 digital camera from the Astro Zoom Collection. A 40X ultra long zoom lens with optical image stabilization delivers crisp, clear 16 megapixel close-ups, 180° panorama or HD videos with the switch of a button. Auto scene, object tracking, post-editing features and a host of powerful yet user-friendly settings make photography with this camera easy, fun and zero hassle. KODAK PIXPRO Digital Cameras – Tell your story.

### FEATURES:

- 40X Optical Zoom
- 24mm Wide Angle
- 16 Megapixels
- 3" LCD (460K Pixels)
- 720p HD Video
- OIS (Optical Image Stabilization)
- AA Battery



Available Colors:

- BLACK
- RED

Images are simulated.



# KODAK PIXPRO AZ401

## DIGITAL CAMERA

| SPECIFICATIONS                               | AZ401  |
|--|--|
| Effective Image Sensor Pixels                | 16.15 Megapixels   |
| Total Image Sensor Pixels                    | 16.44 Megapixels [1/2.3"(CCD)]   |
| Lens   |  |
| Focal Length<br>[ 35mm film equivalent ]     | 4.3 mm (Wide) — 172 mm (Tele)<br>[24 mm (Wide) — 960 mm (Tele)]  |
| F number                                     | F3.0 (Wide) — F6.8 (Tele)  |
| Lens Construction                            | 11 groups 15 elements  |
| Optical Zoom                                 | 40x  |
| Focusing Range                               | Normal: (Wide) 50 cm — ∞, (Tele) 200 cm — ∞<br>Macro: 1.6 cm — ∞ (Wide Only)   |
| Autofocus System                             | TTL Autofocus  |
| Anti-Handshake                               | Optical Image Stabilization  |
| Digital Zoom                                 | 4x Digital Zoom (Combined Zoom: 160x)  |
| Number of Recording Pixels                   |  |
| Still Image                                  | (4:3) 16MP: 4608x3456, 10MP: 3648x2736, 5MP: 2592x1944, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 14MP: 4608x3072, (16:9) 12MP: 4608x2592, 2MP: 1920x1080                          |
| Movie  | 1280x720: 30fps / 15fps, 640x480: 30fps  |
| Image Compression                            | Best, Fine, Normal   |
| DCF, DPOF (Ver1.1) Support                   | Yes  |
| File Format                                  |  |
| Still Image                                  | Exif 2.3 (JPEG)  |
| Movie  | MOV [Image: H.264; Audio: Linear PCM (Monaural)]   |
| Shooting Modes                               | Auto, P, S, A, M, Face Beautifier, Panorama, Movie, CS, SCN [ASCN, Landscape, Sport, Sunset, Fireworks, Night Landscape, Snow, Children, Portrait, Party, Night Portrait, Pet] |
| Detection Features                           | Face, Smile, Blink, Cat, Dog   |
| Photo Touch-up                               | Red-Eye Removal, Skin Soften, Eye Brightening, Eye Enlargement   |
| HDR  | Yes  |
| Panorama                                     | Up to 180° (Horizontal)  |
| LCD Display                                  | 3.0 inch (460K Pixels)   |
| ISO Sensitivity                              | Auto, ISO 80/100/200/400/800/1600/3200 (4M)  |
| AF Method                                    | Single AF, Multi-AF (TTL 9-point), Object Tracking, Face Detection   |
| Exposure Metering Method                     | Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot (Fixed to Center of Frame), Face AE   |
| Exposure Compensation                        | +/- 2EV in 1/3 Step Increments   |
| Shutter Speed                                | 1/2000 - 30 Seconds  |
| Continuous Shooting                          | Yes  |
| Playback Modes                               | Single Photo, Index (9/16 Thumbnails), Slide Show, Date, Zoom (Approx. x2 - x8)  |
| White Balance Control                        | Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Manual, Color Temperature Setting (1900K - 10000K)   |
| Flash  |  |
| Flash Method                                 | Pop-up (Manual)  |
| Flash Modes                                  | Auto, Red-Eye Reduction, Fill Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro, Force Off   |
| Shooting Range                               | (Wide) Approx. 0.5 m - 7.5 m (ISO800); (Tele) Approx. 1.2 m - 3.7 m (ISO800)   |
| Recording Media                              | Internal Memory: Approx. 8MB<br>SD/SDHC Card (Up to 32GB Support) [MMC Card Not Supported]   |
| Other Features                               | Eye-Fi® Compatible, Multi-Language Support (27 Languages)  |
| Jacks  | AV-OUT/USB 2.0 (Micro 5 pin USB), HDMI (Type D)  |
| Power  | AA Alkaline Battery (x4), AA NiMH Battery (x4) (Not Included)  |
| Shooting Capability<br>(Battery Performance) | Approx. 280 Shots (Based on CIPA Standards)  |
| Operation Environment                        | Temperature: 32° - 104°F / 0° - 40°C, Humidity: 0 - 90%  |
| Dimensions (WxHxD)                           | Approx. 4.5 x 3.21 x 3.32 in. / 114.3 x 81.6 x 84.4 mm (Based on CIPA Standards)   |
| Weight                                       | Approx. Approx. 15.37 oz. / 436g (Body Only)   |
| Supplied Accessories                         | AA Alkaline Battery (x4), Neck Strap, Lens Cover, Quick Start Guide, Warranty Card, Service Card   |

## JK Imaging Ltd.

17239 So. Main Street, Gardena, CA 90248  
(888) 978-0806

To learn more about KODAK PIXPRO Digital Cameras:  
visit: [kodakpixpro.com](http://kodakpixpro.com)

© 2023 JK Imaging, Ltd. The Kodak trademark, logo and trade dress are used under license from Eastman Kodak Company. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. All information contained in this document is subject to change without notice. Document Number/Sequence: U.DIS.0056.0919.en.06

