KODAK PIXPRO AZ405

DIGITAL CAMERA



AZ405 ASTRO ZOOM

Passion and performance go hand in hand with our KODAK PIXPRO AZ405 digital camera from the Astro Zoom Collection. A 40x ultra long zoom lens with optical image stabilization delivers crisp, clear 20 megapixel close-ups, panorama or HD videos. Auto scene, object tracking, post-editing features and a host of powerful yet user-friendly settings make photography easy, fun and zero hassle. KODAK PIXPRO Digital Cameras – Tell your story.

FEATURES:

- 40X Optical Zoom
- 24mm Wide Angle
- 20 Megapixels
- 3" LCD (460K Pixels)
- 1080p Full HD Video
- OIS (Optical Image Stabilization)
- AA Battery















Available Colors:

BLACK

RED

) WHITE

Images are simulat



KODAK PIXPRO AZ405

DIGITAL CAMERA

SPECIFICATIONS	AZ405
Effective Image Sensor Pixels	20.68 Megapixels
Total Image Sensor Pixels	21.14 Megapixels [1/2.3" BSI CMOS]
Lens	
Focal Length	4.3 mm (Wide) — 172 mm (Tele)
[35mm film equivalent]	[24 mm (Wide) — 960 mm (Tele)]
F number	F3.0 (Wide) — F6.8 (Tele)
Lens Construction	11 groups 15 elements
Optical Zoom	40x
Focusing Range	Normal: (Wide) 50 cm $-\infty$, (Tele) 200 cm $-\infty$ Macro: 1.6 cm $-\infty$ (Wide Only)
Autofocus System	TTL Autofocus
Anti-Handshake	Optical Image Stabilization
Digital Zoom	4x Digital Zoom (Combined Zoom: 160x)
Number of Recording Pixels Still Image	(4:3) 20MP: 5184x3888, 10MP: 3648x2736, 5MP: 2592x1944, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 18MP: 5184x3456, (16:9) 15MP: 5120x2880, 2MP: 1920x1080
Movie	1920x1080: 30fps, 1280x720: 60fps / 30fps, 640x480: 30fps, High-Speed Movie 640x480: 120fps
Image Compression	Best, Fine, Normal
DCF, DPOF (Ver1.1) Support	Yes
File Format Still Image	Exif 2.3 (JPEG)
Movie	MOV [Image: Motion JPEG; Audio: Linear PCM (Monaural)]
Shooting Modes	Auto, P, S, A, M, Face Beautifier, Panorama, Movie, CS, SCN [ASCN, Landscape, Sport, Beach, Sunset, Fireworks, Night Landscape, Snow, Children, Portrait, Party, Night Portrait, Pet]
Detection Features	Face, Smile, Blink, Cat, Dog
Photo Touch-up	Red-Eye Removal, Skin Soften, Eye Brightening, Eye Enlargement
HDR	Yes
Scan Panorama	Up to 360°
LCD Display	3.0 inch (460K Pixels)
ISO Sensitivity	Auto, ISO 100/200/400/800/1600/3200
AF Method	Single AF, Multi-AF (TTL 9-point), Object Tracking, Face Detection
Exposure Metering Method	Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot (Fixed to Center of Frame), Face AE
Exposure Control Method	Program AE (AE-Lock Available), Shutter Prior AE, Apeture Prior AE
Exposure Compensation	+/- 3EV in 1/3 Step Increments
Shutter Speed	1/2000 ~ 30 Seconds
Continuous Shooting	Yes
Playback Modes	Single Photo, Index (9/16 Thumbnails), Slide Show, Date, Burst Shooting, Zoom (Approx. x2 ~ x8)
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Manual, Color Temperature Setting (1900K - 10000K)
Flash	
Flash Method Flash Modes Shooting Range	Pop-up (Manual) Auto, Red-Eye Reduction, Fill Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro, Forced Off (Wide) Approx. 0.5 m – 7.5 m (ISO800); (Tele) Approx. 2.0 m – 3.7 m (ISO800)
Recording Media	Internal Memory: Approx. 67MB SD/SDHC/SDXC Card (Up to 512GB Support) [MMC Card Not Supported]
Other Features	Multi-Language Support (27 Languages)
Jacks	USB 2.0 (Micro 5 pin USB)
Power	AA Alkaline Battery (x4), AA NiMH Battery (x4) (Not Included)
Shooting Capability (Battery Performance)	Approx. 300 Shots (Based on CIPA Standards) Approx. 120 min for Video (@ 1080 / 30 fps)
Operation Environment	Temperature: 32° – 104°F / 0° – 40°C, Humidity: 0 – 90%
Dimensions (WxHxD)	Approx. 4.50 x 3.21 x 3.32 in. / 114.3 x 81.6 x 84.4 mm (Based on CIPA Standards)
Weight	Approx. 15.37 oz. / 436g (Body Only)
Supplied Accessories	AA Alkaline Battery (x4), USB Cable, Neck Strap, Lens Cover, Service Card, Quick Start Guide, Warranty Card

JK Imaging Ltd.

To learn more about KODAK PIXPRO Digital Cameras:

visit: kodakpixpro.com

17239 So. Main Street, Gardena, CA 90248 (888) 978-0806

© 2023 JK Imaging, Ltd. The Kodak trademark, logo and trade dress are used under license from Eastman Kodak Company. All information contained in this document is subject to change without notice. Document Number/Sequence: U.DIS.0070.0923.en.02











